



109 Kero Road, Carlstadt, NJ 07072  
T: (718) 599-5112 F: (718) 387-7941  
[www.DoorStopNY.com](http://www.DoorStopNY.com)

# PRODUCT DATA SHEET

# "Diet" CORE

## SPECIFICATIONS

**Maximum Size:** Up to 72" x 108" or up to 48" x 144", depending upon veneer and face availability. Call office for information.

**Thickness:** 1.375", 1.75", 2" and 2.25"

**Core:** Light-weight natural wood.

**Veneers & Faces:** Our entire collection of natural wood veneers and engineered faces are available (see [www.DoorStopNY.com](http://www.DoorStopNY.com))

**Stiles:** 1.25" softwood stiles are standard. Matching hardwood stiles with SCL backer (used for rigidity) are also available. All dimensions prior to factory trimming and prefitting.

**Rails:** Wood rails are standard mill option. Hardwood available upon request. All dimensions prior to factory trimming and prefitting.

**Finish:** TR-6 UV clear, custom stain to match color, or primed where applicable.

**Adhesive:** PVA meets or exceeds WDMA I.S. I-A for Type I flush wood door adhesive.

**Lites:** Wood lip or flush moulding wood visions and metal vision frames with ¼" glass (all types).

**Blocking:** Top rail, bottom rail, stiles and blocking for special hardware is available.

**Machining:** Bevel, hinge and lock, mortise lock, card lock, pivot and other hardware preps using state-of-the-art CNC equipment.

### Environmental / LEED Credit Contributions (Optional)

- Rapidly Renewable Materials
- Certified Wood (FSC Pure, FSC % and FSC CW)
- Low Emitting Materials / No Added Urea Formaldehyde



"Diet" Core Code	Door Thickness	"Diet" Core Avg. Lbs./Sq. Ft.	Particle Core Avg. Lbs./Sq. Ft.	SCL/LSL Core Avg. Lbs./Sq. Ft.
D8	1.375"	1.67	3.13	3.88
D4	1.75"	2.12	4.25	5.38
D2	2"	2.42	4.88	6.13
D1	2.25"	2.72	5.50	7.00

Weight is based off of the "Diet" Core only, not including stiles and rails.